

FIAT SERVICE LETTER

SUBJECT: COLD STARTING KITS

VEHICLE: 1975-76 X 1/9

CONDITION: Hard starting in cold weather.

CORRECTION: In order to eliminate this condition, a cold starting kit has been made available for installation in the above-mentioned vehicles. This kit consists of a new ignition coil, ignition wire set and a set of spark plugs. This kit is to be installed only if the customer specifically complains of hard starting when the vehicle is cold.

A copy of the instructions for the installation of this kit has been attached to this letter for your review. (Installation instructions will also be included in each kit.) All components included in this kit must be installed in the vehicle.

WARRANTY INFORMATION:

Installation of this cold starting kit is to be performed free of charge for the owner of the vehicle. Your dealership will be reimbursed for both parts and labor when one of the enclosed repair cards is sent back, properly filled out and signed by the owner of the vehicle.* Additional repair cards are available from your Regional Parts & Service Manager.

*All parts that have been replaced must be properly tagged and held for inspection by your Fiat Zone Parts & Service Manager.

The total time allowance for the installation of the cold starting kit is .5 hours.

PARTS INFORMATION:

The cold starting kit must be ordered from your local parts depot. These kits will be charged \$33.79 to your account and subsequently credited with a 25% mark-up when the properly filled out repair cards are sent back.

READ, INITIAL AND PASS ON

Service Manager	Parts Manager	Service Writer	Technician			

Please note that repair cards to be used for the X 1/9 model are identical to those repair cards used for 128 models. The part item "ground cable" is to be disregarded for the X 1/9 model.

The part number for the cold starting kit is #4719.

NOTE: Canadian dealers should send the repair cards filled out to:

Fiat Canada
1750 Brimley Road
Scarborough, Ontario
Attn: Service Department



(SC-025)

Year	Vehicle I.D. Number	Model
------	---------------------	-------

THE FOLLOWING PARTS WERE REPLACED ON MY CAR AT NO COST TO MYSELF.

- GROUND CABLE
- COIL

- SPARK PLUGS
- COIL AND SPARK PLUG WIRES

Acct # of Dealer performing the modification

Vehicle owner

**Parts Required**

Ignition coil
(4) spark plugs
Coil wire
Spark plug wire set

Tools Required

8 mm open wrench or socket
10 mm open wrench or socket
spark plug socket
ratchet
extension

(All parts are included in kit)

Remove coil to distributor wire. Remove spark plug wires.
Remove coil. Replace with new coil. Remove spark plugs. Set gap on new spark plugs to 0.5 to 0.6 mm (0.020 to 0.024 in.). Install new plugs. Install new coil to distributor wire. Install new spark plug wires. Operate engine and check timing.

